



Goupilles cylindriques rectifiées acier (sachet de 5) DIN 6325 - ISO 8734 - NFE 27475

Goupilles cylindriques rectifiées en acier trempé 58-62HRC



Marque : GARDETTE INDUSTRIE

Référence : 0G20031-5

Prix : 0.00€

Options disponibles :

Diamètre-Longueur-2026 : 12m6X120 (+ 10.92€), 12m6X130, 12m6X140 (+ 13.68€), 12m6X150, 12m6X160 (+ 37.80€), 14m6X20 (+ 7.08€), 14m6X24 (+ 6.36€), 14m6X26, 14m6X28 (+ 6.36€), 14m6X30 (+ 7.20€), 14m6X32 (+ 7.80€), 14m6X36 (+ 8.04€), 14m6X40 (+ 8.16€), 14m6X45 (+ 8.64€), 14m6X50 (+ 9.00€), 14m6X55 (+ 9.24€), 14m6X60 (+ 9.48€), 14m6X70 (+ 10.56€), 14m6X80 (+ 10.80€), 14m6X90 (+ 12.36€), 14m6X100 (+ 13.56€), 14m6X120 (+ 18.48€), 14m6X130 (+ 20.40€), 14m6X140 (+ 21.36€), 14m6X150, 14m6X160 (+ 38.64€), 16m6X24 (+ 8.16€), 16m6X26, 16m6X28 (+ 7.92€), 16m6X30 (+ 8.04€), 16m6X32 (+ 8.16€), 16m6X36 (+ 8.40€), 16m6X40 (+ 8.88€), 16m6X45 (+ 9.24€), 16m6X50 (+ 9.72€), 16m6X55 (+ 10.68€), 16m6X60 (+ 11.28€), 16m6X70 (+ 12.12€), 16m6X80 (+ 13.20€), 16m6X90 (+ 14.52€), 16m6X100 (+ 16.32€), 16m6X120 (+ 19.20€), 16m6X130 (+ 22.80€), 16m6X140 (+ 24.24€), 16m6X150 (+ 25.80€), 16m6X160 (+ 41.88€), 18m6X40 (+ 12.96€), 18m6X45 (+ 13.08€), 18m6X50 (+ 13.20€), 18m6X55 (+ 14.28€), 18m6X60 (+ 14.76€), 18m6X70 (+ 16.32€), 18m6X80 (+ 19.20€), 18m6X90 (+ 21.60€), 18m6X100 (+ 23.16€), 18m6X120 (+ 26.88€), 18m6X130, 18m6X140 (+ 32.28€), 18m6X150, 18m6X160 (+ 59.28€), 20m6X30 (+ 14.52€), 20m6X32 (+ 14.52€), 20m6X36 (+ 15.00€), 20m6X40 (+ 15.60€), 20m6X45 (+ 16.32€), 20m6X50 (+ 16.80€), 20m6X55 (+ 18.48€), 20m6X60 (+ 18.60€), 20m6X70 (+ 20.40€), 20m6X80 (+ 21.48€), 20m6X90 (+ 25.20€), 20m6X100 (+ 26.28€), 20m6X120 (+ 30.24€), 20m6X130 (+ 33.84€), 20m6X140 (+ 35.28€), 20m6X150 (+ 48.36€), 20m6X160 (+ 63.60€), 25m6X50 (+ 36.24€), 25m6X55 (+ 39.96€), 25m6X60 (+ 39.96€), 25m6X70 (+ 45.00€), 25m6X80 (+ 49.68€), 25m6X90 (+ 53.04€), 25m6X100 (+ 56.16€)

Descriptif :

Désignation : goupilles cylindriques rectifiées

Normes usuelles : DIN 6325, ISO 8734

Normes équivalentes : NFE 27475

Matière de la norme : Acier trempé 58-62HRC

Commentaires : diamètre rectifié m6. Autres matières et autres tolérances possibles

[Lien vers la fiche du produit](#)